



N51

Plaque isolante P = 600 N/mm²

exemple de commande:
1 pièce N51 95/95/3/22



Température d'utilisation : 200°C
Conductivité thermique : 0,19 W/mk
Masse volumique : 1,9 g/cm²



b	l	S	D	
95	95	3	22	•
100	130		22	•
156	156		90	•
	196		90	•
	246		90	•
190	246		90	•
196	196		90	•
	246		90	•
206	156		90	•
	196		90	•
95	95	5	22	•
100	130		22	•
156	156		90	•
	196		90	•
	246		90	•
	296		90	•
	396		90	•
190	246		90	•
	296		90	•
196	196		90	•
	246		90	•
	296		90	•
	346		90	•
206	156		90	•
	196		90	•
218	246		90	•
	296		90	•
246	246		90	•
	296		90	•
	346		90	•
	396		90	•
254	246		90	•
276	246		90	•

b	l	S	D	
126	156	6	90	•
	246		90	•
156	156		90	•
	196		90	•
	206		90	•
	246		90	•
	296		90	•
	346		90	•
	396		90	•
	446		90	•
196	196		90	•
	206		90	•
	246		90	•
	296		90	•
	346		90	•
	396		90	•
	446		90	•
	496		90	•
216	246		90	•
	296		90	•
	396		90	•
246	246		90	•
	266		90	•
	296		90	•
	346		90	•
	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
266	296		90	•

N51

Plaque isolante P = 600 N/mm²

exemple de commande:
1 pièce N51 196/296/7/90



Température d'utilisation : 200°C
Conductivité thermique : 0,19 W/mk
Masse volumique : 1,9 g/cm²




b	l	S	D	
196	296	7	90	•
	346		90	•
	396		90	•
	446		90	•
218	396		90	•
246	246		90	•
	296		90	•
	346		90	•
	396		90	•
	446		90	•
254	246		90	•
276	296		90	•
296	296		90	•
	346		90	•
	396		90	•
	446		90	•
346	346		90	•
	396		90	•
	446		90	•
	496		90	•
	546		90	•
396	396		90	•
	446		90	•
	496		90	•
	546		90	•
496	546		90	•
296	296	8	90	•
	346		90	•
	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
	646		90	•
	696		90	•

b	l	S	D	
346	346	8	90	•
	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
	646		90	•
	696		90	•
396	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
	646		90	•
	696		90	•
	796		90	•
446	446		90	•
	496		90	•
	546		90	•
	596		90	•
	646		90	•
	696		90	•
	796		90	•
496	496		90	•
	546		90	•
	596		90	•
	646		90	•
	696		90	•
	796		90	•
546	546		90	•
	596		90	•
	646		90	•
	696		90	•
	796		90	•
596	596		90	•
	646		90	•
	696		90	•
	796		90	•
646	646		90	•
	696		90	•
	796		90	•

N51

Plaque isolante P = 600 N/mm²

exemple de commande:
1 pièce N51 246/496/8,5/90



Température d'utilisation : 200°C
Conductivité thermique : 0,19 W/mk
Masse volumique : 1,9 g/cm²

b	l	S	D	
246	496	8.5	90	•
296	296		90	•
	346		90	•
	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
	696		90	•
	796		90	•
346	346		90	•
	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
	696		90	•
	796		90	•
396	396		90	•
	446		90	•
	496		90	•
	546		90	•
	596		90	•
	696		90	•
	796		90	•
	896		90	•
446	446		90	•
	496		90	•
	546		90	•
	596		90	•
	696		90	•
	796		90	•
	896		90	•
496	496		90	•
	546		90	•
	596		90	•
	696		90	•
	796		90	•
	896		90	•
	996		90	•

b	l	S	D	
546	546	8.5	90	•
	596		90	•
	646		90	•
	696		90	•
	796		90	•
	896		90	•
	996		90	•
596	596		90	•
	696		90	•
	796		90	•
	896		90	•
646	596		90	•
	696		90	•
	796		90	•
	896		90	•
696	696		90	•
	796		90	•
	896		90	•
	996		90	•
796	796		90	•
	896		90	•
	996		90	•
896	896		90	•
	996		90	•