



N52

Plaque isolante P = 330 N/mm²

exemple de commande:
1 pièce N52 95/95/3



Température d'utilisation : 200°C
Conductivité thermique : 0,18 W/mk
Masse volumique : 1,8 g/cm³



b	l	S	D	
95	95	3	-	•
100	130			•
156	156			•
	196			•
	246			•
	296			•
	396			•
190	246			•
	296			•
196	196			•
	246			•
	296			•
	346			•
206	156			•
	196			•
218	246			•
	296			•
246	246			•
	296			•
254	246			•
276	246			•
	296			•
296	296			•
95	95	5		•
100	130			•
156	156			•
	196			•
	246			•
	296			•
	396			•
190	246			•
	296			•
196	196			•
	246			•
	296			•
	346			•
	396			•
	446			•
206	156			•
	196			•
218	246			•
	296			•
	396			•

b	l	S	D	
246	246	5	-	•
	296			•
	346			•
	396			•
	446			•
	496			•
254	246			•
276	246			•
296	296			•
	346			•
	396			•
	446			•
	496			•
	546			•
	596			•
346	346			•
	396			•
	446			•
	496			•
	546			•
396	396			•
	446			•
	496			•
126	156	6		•
	246			•
156	156			•
	196			•
	206			•
	246			•
	296			•
	346			•
	396			•
	446			•
196	196			•
	206			•
	246			•
	296			•
	346			•
	396			•
	446			•
	496			•
216	246			•
	296			•

N52

Plaque isolante P = 330 N/mm²

exemple de commande:
1 pièce N52 216/396/6



Température d'utilisation : 200°C
Conductivité thermique : 0,18 W/mk
Masse volumique : 1,8 g/cm²




b	l	S	D	
216	396	6	-	•
246	246			•
	266			•
	296			•
	346			•
	396			•
	446			•
	496			•
	546			•
	596			•
266	296	7		•
196	296			•
	346			•
	396			•
218	396			•
	246			•
	296			•
246	346			•
	396			•
	446			•
254	246			•
276	296			•
296	296			•
	346			•
	396			•
	446			•
346	346			•
	396			•
	446			•
	496			•
396	546			•
	396			•
	446			•
	496			•
496	546	8		•
296	296			•
	346			•
	396			•
	446			•
	496			•
	546			•

b	l	S	D	
296	596	8	-	•
346	646			•
	696			•
	346			•
	396			•
	446			•
	496			•
	546			•
	596			•
	646			•
396	696			•
	796			•
	396			•
	446			•
	496			•
	546			•
	596			•
	646			•
	696			•
446	796			•
	446			•
	496			•
	546			•
	596			•
	646			•
	696			•
	796			•
	796			•
496	496			•
	546			•
	596			•
	646			•
	696			•
	796			•
	796			•
	546			•
	596			•
546	646			•
	696			•
	796			•
	796			•
	596			•
	646			•
	696			•
	796			•
	896			•

N52

Plaque isolante P = 330 N/mm²

exemple de commande:
1 pièce N52 596/996/8



Température d'utilisation : 200°C
Conductivité thermique : 0,18 W/mk
Masse volumique : 1,8 g/cm²

b	l	S	D	
596	996	8	-	•
646	646			•
	696			•
	796			•
	896			•
	996			•
696	696			•
	746			•
	796			•
	896			•
	996			•
746	796			•
	896			•
	996			•
796	796			•
	846			•
	896			•
	996			•
846	896			•
	996			•
246	496	8.5		•
296	296			•
	346			•
	396			•
	446			•
	496			•
	546			•
	596			•
	696			•
346	346			•
	396			•
	446			•
	496			•
	546			•
	596			•
	696			•
	796			•
396	396			•
	446			•
	496			•
	546			•
	596			•
	696			•

b	l	S	D	
396	796	8.5	-	•
446	896			•
	446			•
	496			•
	546			•
	596			•
	696			•
	796			•
	896			•
496	496			•
	546			•
	596			•
	696			•
	796			•
	896			•
	996			•
546	546			•
	596			•
	646			•
	696			•
	796			•
	896			•
	996			•
596	596			•
	696			•
	796			•
	896			•
	996			•
	646			•
	696			•
646	596			•
	696			•
	796			•
	896			•
	996			•
	696			•
	796			•
696	696			•
	796			•
	896			•
	996			•
796	796			•
	896			•
	996			•
896	896			•
	996			•